

SMQ-4301 4K SURVEILLANCE MONITOR WITH BNC


FEATURES



- 4K UHD 3840 x 2160 resolution
- Anti-Burn-in™ technology prevents image ghosting
- Image Enhancer: 3D Comb Filter / Deinterlace / Noise Reduction
- Versatile connectivity: HDMI, DVI, VGA, Composite (BNC)
- BNC passive loop-through output port
- RS232/LAN Control - provides compatibility with control systems
- Black-level adjustment for presenting more details in dark images
- Selectable gamma curves optimise different kinds of images
- CCTV picture mode for maximum image detail in low light footage
- Optional blue or black screen when no input signal is detected
- Lockable control keys to prevent tampering in public environments
- Commercial-grade panel for high reliability and long product lifetime
- 24/7 Operation with a rugged metal housing design

The SMQ-4301 is a durable 43-inch 4K surveillance display. The display technology is future-proof and compatible with both analogue and digital surveillance systems. It provides 24/7 nonstop operation in the control rooms. The display supports up to 8MP camera image quality and can present crisp video footage, especially when zooming in the images for further detail checking. This level of image quality promotes more efficient and accurate video surveillance analysis. The SMQ-4301 features AG Neovo patented Anti-Burn-in™ Technology, preventing LCD burn-in during a surveillance operation. The technology also includes PID command & Ctrl software for easy management of multiple displays in security environments.

TECHNICAL DRAWING



SPECIFICATIONS

Panel	
Panel Type	LED-Backlit TFT LCD (IPS Technology)
Panel Size	43"
Max. Resolution	UHD 3840 x 2160
Pixel Pitch	0.245 mm
Brightness	350 cd/m ²
Contrast Ratio	1200:1
Viewing Angle (H/V)	178° / 178°
Display Colour	1.07B
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 1%), 3H Hard Coating
Frequency	
Frequency (H)	15KHz~ 135KHz
Frequency (V)	24Hz ~ 86 Hz
Signal Input	
HDMI	2.0 x 1
DVI	24-Pin DVI-D
VGA	15-Pin D-Sub x 1
Composite	BNC x 1
Signal Output	
Composite	BNC x 1
External Control	
RS232 In	9-Pin D-Sub
LAN	RJ45 x 1
Other Connectivity	
USB	2.0 x 1 (Service Port)
Audio	
Audio In	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (3.5 mm), SPDIF
Internal Speakers	5 W x 2
Power	
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	67W
Standby Mode	< 0.5W
Off Mode	< 0.3W
Power Supply	Internal
Operating Conditions	
Temperature	0° C-40° C (32° F-104° F)
Humidity	20%-85% (non-condensing)
Storage Conditions	
Temperature	-10° C-60° C (-4° F-140° F)
Humidity	10%-95% (non-condensing)
Mounting	
VESA FPMPI	Yes (400 x 200 mm)
Dimensions	
Product w/o Base (W x H x D)	969.9 x 558.3 x 84.6 mm (38.2" x 22.0" x 3.3")
Packaging (W x H x D)	1070.0 x 663.0 x 153.0 mm (42.1" x 26.1" x 6.0")
Weight	
Product w/o Base	9.0 kg (19.8 lb)
Packaging	11.7 kg (25.4 lb)
Regulation Approval	
Certifications & Compliance	CE, LVD, WEEE, RoHS, REACH, EAC, UKCA
Accessories	
Supplied	Power Cord, HDMI Cable, Remote Control, Batteries, Quick Start Guide
Optional Accessories	
Video Wall Mount	VWM-01, VWM-02
Ceiling Mount (Landscape only)	CMP-01+ LMK-01, CMP-01+ LMK-02
Wall Mount (Landscape only)	LMA-01, LMK-01, LMK-02, LMK-03, LMA-02
Floor Mount (Landscape only)	FMS-01, FMS-02, FMC-02
Desk mount (Landscape only)	DTS-01

